



# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

**Product number** 208-003  
**Product name** **Toner Aide**  
**Effective date** 06-Jun-2011  
**Company information** Sprayway, Inc.  
1005 Westgate  
Addison, IL 60101 United States  
**Company phone** General Assistance 630-543-7600  
**Emergency telephone US** 800-424-9300  
**Emergency telephone outside US** 703-527-3887  
**Version #** 04  
**Supersedes date** 28-Dec-2007

## 2. Hazards Identification

**Emergency overview** Will be easily ignited by heat, spark or flames.  
Cancer hazard. Irritating to skin. Irritating to eyes. Irritating to respiratory system.  
Prolonged exposure may cause chronic effects. EXTREMELY FLAMMABLE  
CONTENTS UNDER PRESSURE. Aerosol.

**Potential health effects**

**Routes of exposure** Inhalation. Skin contact. Ingestion.

**Eyes** Causes eye irritation.

**Skin** This product may be harmful if it is absorbed through the skin. Irritating to skin.  
Prolonged or repeated contact can result in defatting and drying of the skin which may  
result in skin irritation and dermatitis (rash).

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal.  
Irritating to respiratory system. Prolonged inhalation may be harmful.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.  
Components of the product may be absorbed into the body by ingestion.

**Target organs** 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is  
repeated and prolonged and may cause blood damage. These effects have not been  
observed in humans.  
Central nervous system. Lungs.

**Chronic effects** Unconsciousness. May cause central nervous system disorder (e.g., narcosis involving a  
loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or  
damage. May cause delayed lung damage. Prolonged skin contact may defat the skin  
and produce dermatitis.

**Signs and symptoms** Discomfort in the chest. Narcosis. Cyanosis. Jaundice. Defatting of the skin. Irritation.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	20 - 30
n-Butyl Acetate	123-86-4	20 - 30
Trichloroethylene	79-01-6	15 - 20
Propane	74-98-6	10 - 15
Acetone	67-64-1	10 - 15
Stoddard Solvent	8052-41-3	1 - 3
2-Butoxyethanol	111-76-2	1 - 3
Non-hazardous and other components below reportable levels		1 - 2.5

## 4. First Aid Measures

### First aid procedures

<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.
<b>Skin contact</b>	Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops or persists. For minor skin contact, avoid spreading material on unaffected skin.
<b>Inhalation</b>	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If symptoms persist, get medical attention.
<b>Ingestion</b>	If material is ingested, immediately contact a poison control center. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
<b>Notes to physician</b>	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

## 5. Fire Fighting Measures

<b>Flammable properties</b>	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Alcohol foam. Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Do not use water jet. Water may be ineffective.
<b>Protection of firefighters</b>	
<b>Specific hazards arising from the chemical</b>	Fire may produce irritating, corrosive and/or toxic gases.
<b>Protective equipment and precautions for firefighters</b>	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

## 6. Accidental Release Measures

<b>Methods for containment</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.
<b>Methods for cleaning up</b>	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

## 7. Handling and Storage

<b>Handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.
<b>Storage</b>	Level 2 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Level 2 Aerosol. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

## 8. Exposure Controls / Personal Protection

### Exposure limits

#### ACGIH

Components	CAS #	TWA	STEL	Ceiling
n-Butane	106-97-8	1000 ppm	Not established	Not established
n-Butyl Acetate	123-86-4	150 ppm	200 ppm	Not established
Trichloroethylene	79-01-6	10 ppm	25 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Stoddard Solvent	8052-41-3	100 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established

#### OSHA

Components	CAS #	TWA	STEL	Ceiling
n-Butyl Acetate	123-86-4	150 ppm	Not established	Not established
Trichloroethylene	79-01-6	100 ppm	Not established	200 ppm
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Stoddard Solvent	8052-41-3	500 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established

### Personal protective equipment

<b>Eye / face protection</b>	Wear chemical goggles.
<b>Skin protection</b>	Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

## 9. Physical & Chemical Properties

<b>Appearance</b>	Compressed liquefied gas.
<b>Boiling point</b>	114.8 °F (46.1 °C) estimated
<b>Color</b>	clear colorless
<b>Density</b>	0.7486 g/cm3 estimated
<b>Flammability (HOC)</b>	29.3282 kJ/g estimated
<b>Flash back</b>	Yes
<b>Flash point</b>	-156 °F (-104.4 °C) Propellant
<b>Form</b>	Liquid. Aerosol.
<b>Freezing point</b>	Not available
<b>Odor</b>	fruity
<b>pH</b>	Not applicable
<b>Physical state</b>	Liquid.
<b>Pressure</b>	50 - 70 psig @ 70F
<b>Solubility</b>	Negligible
<b>Specific gravity</b>	0.7487 estimated

## 10. Chemical Stability & Reactivity Information

<b>Chemical stability</b>	Risk of ignition.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Hazardous decomposition products</b>	Irritants. Toxic gas. May include oxides of nitrogen.

## 11. Toxicological Information

<b>Acute effects</b>	Acute LD50: 7292 mg/kg estimated, Rat, Dermal
----------------------	---

Product name: Toner Aide

Product #: 208-Toner Aide

MSDS US

3 / 6

## Component analysis - LD50

### Toxicology Data - Selected LD50s and LC50s

2-Butoxyethanol	111-76-2	Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat 470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg
Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
n-Butyl Acetate	123-86-4	Inhalation LC50 Rat 390 ppm 4 h; Oral LD50 Rat 10768 mg/kg; Dermal LD50 Rabbit >17600 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Trichloroethylene	79-01-6	Inhalation LC50 Rat 8000 ppm 4 h; Inhalation LC50 Rat 26300 ppm 1 h; Oral LD50 Rat 4290 mg/kg; Dermal LD50 Rabbit >20 g/kg

**Sensitization** Not expected to be hazardous by OSHA criteria.

**Carcinogenicity** Hazardous by OSHA criteria.

### IARC - Group 2A (Probably Carcinogenic to Humans)

Trichloroethylene 79-01-6 Monograph 63 [1995]; Supplement 7 [1987]

**Teratogenicity** Not expected to be hazardous by OSHA criteria.

## 12. Ecological Information

**Ecotoxicity** Components of this product are hazardous to aquatic life.

LC50 56.29 mg/L estimated, Fish, 96.00 Hours,  
EC50 12.21 mg/L estimated, Daphnia, 48.00 Hours,  
IC50 810 mg/L estimated, Algae, 72.00 Hours,

## 13. Disposal Considerations

**Waste codes** D001: Waste Flammable material with a flash point <140 F  
D040: Waste Trichloroethylene

**Disposal instructions** Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

## 14. Transport Information

### Department of Transportation (DOT) Requirements

#### Basic shipping requirements:

**Proper shipping name** Consumer commodity  
**Hazard class** ORM-D  
**Subsidiary hazard class** None

#### Additional information:

**Packaging exceptions** 156, 306  
**Packaging non bulk** 156, 306  
**Packaging bulk** None

### IMDG

#### Basic shipping requirements:

**Proper shipping name** AEROSOLS, toxic, flammable  
**Hazard class** 2.1  
**UN number** 1950

#### Additional information:

**Packaging exceptions** NOT a LTD QTY  
**Item** 5TF  
**Labels required** 2.1  
+6.1

**Transport Category** If <1L: Consumer Commodity



**IATA****Basic shipping requirements:**

**Proper shipping name** Aerosols, flammable, containing substances in Division 6.1, Packing Group III

**Hazard class** 2.1

**Subsidiary hazard class** 6.1

**UN number** 1950

**Additional information:**

**Packaging exceptions** LTD QTY

**Labels required** 2.1, 6.1



<b>15. Regulatory Information</b>
-----------------------------------

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

2-Butoxyethanol	111-76-2	1.0 % de minimis concentration (applies to R-(OCH <sub>2</sub> CH <sub>2</sub> ) <sub>n</sub> -OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)
Trichloroethylene	79-01-6	0.1 % de minimis concentration

**Occupational Safety and Health Administration (OSHA)**

**29 CFR 1910.1200 hazardous chemical** Yes

**CERCLA (Superfund) reportable quantity**

n-Butyl Acetate: 5000.0000  
 Trichloroethylene: 100.0000  
 Acetone: 5000.0000

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Section 302 extremely hazardous substance** No

**Section 311 hazardous chemical** Yes

**Hazard categories (311/312)** Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations**

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**U.S. - Pennsylvania - RTK (Right to Know) List**

2-Butoxyethanol	111-76-2	Present
Acetone	67-64-1	Environmental hazard
n-Butane	106-97-8	Present
n-Butyl Acetate	123-86-4	Environmental hazard
Propane	74-98-6	Present
Stoddard Solvent	8052-41-3	Present
Trichloroethylene	79-01-6	Environmental hazard

<b>16. Other Information</b>
------------------------------

**Further information**

HMIS® is a registered trade and service mark of the NPCA.

**HMIS® ratings**

Health: 2\*  
Flammability: 3  
Physical hazard: 0

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication, The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification, The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**MSDS sections updated  
Prepared by**

This document has undergone significant changes and should be reviewed in its entirety.  
Regulatory Compliance