

**MATERIAL SAFETY DATA SHEET**

**1: CHEMICAL PRODUCT IDENTIFICATION**

Product Name: Aqua Wash 30  
 Product Code: AquaW30 B10010  
 MSDS Date: August 29, 2007

**2: COMPOSITION, INFORMATION ON INGREDIENTS**

No.	Component CAS REG. NO.	Amount %	OSHA		ACGIH	
			PEL	STEL	TLV	STEL
1	Dimethyl Esters Mixture	25 - 30	NE	NE	NE	NE
2	Water	15 - 20	NE	NE	NE	NE
3	7732-18-5 ~2-Propoxyethanol	20 - 25	NE	NE	NE	NE
4	2807-30-9 Propylene Glycol Ethers Mixture	30 - 35	NE	NE	NE	NE
5	Butoxydiethylene Glycol 112-34-5	5 - 10	NE	NE	NE	Ne
6	2-Butoxyethanol 111-76-2	3 - 6	50 ppm	skin	20 ppm	
7	d'Limonene 138-86-3 5989-27-5 94266-47-4	3 - 6	NE	NE	NE	NE

**3: HAZARDS IDENTIFICATION**

**EMERGENCY RESPONSE INFORMATION**

HAZARDS	HMIS	NFPA
Toxicity	1	1
Fire	2	2
Reactivity	0	0
Special	B	

RATING	DEGREE OF HAZARD
4	Extreme
3	High
2	Moderate
1	Slight
0	Insignificant

SPECIAL EQUIPMENT LEGEND			
A	Safety Glasses	F	C + Dust Mask
B	A + Gloves	G	B + Respirator
C	B + Apron	H	F + Goggles
D	C + Face Shield	I	B + Respirator
E	B + Dust Mask	X	Ask Supervisor

Caution! Potentially combustible liquid and vapor. Harmful if inhaled. High vapor concentrations may cause dizziness. May cause skin irritation. May causes eye irritation. Harmful if swallowed. Pulmonary aspiration hazard: can enter lungs and cause damage.

**HEALTH EFFECTS FROM OVEREXPOSURE**

Primary Routes of Exposure  
 Skin Contact

Eye Contact  
Inhalation  
Ingestion

**Eye Contact:**

Direct contact with material can cause irritation, pain and transient injury.

**Skin Contact:**

May cause irritation with prolonged or repeated contact. Removes natural oils and fats from skin.

**Inhalation:**

Inhalation of mist or spray can cause irritation to nose, throat and lungs, and higher concentrations may cause headaches, nausea, dizziness, drowsiness.

**Ingestion:**

This material is of a low order of toxicity. It may cause headache, dizziness, gastrointestinal distress.

---

#### **4: FIRST AID MEASURES**

**Inhalation:**

Remove subject to fresh air. Keep subject at rest. If not breathing, give artificial respiration and obtain medical assistance.

**Eye Contact:**

Immediately flush eyes with a large amount of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissues. Remove contact lenses if worn. Consult a physician if irritation persists.

**Skin Contact:**

Wash affected skin areas thoroughly with soap and water for 15 minutes until no odor remains. If redness or swelling develops, consult a physician. Immediately remove contaminated clothing and wash before reuse.

**Ingestion:**

**NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.** Have person drink several glasses of water. Do not induce vomiting. Keep airway clear. Keep subject at rest. Obtain Emergency Medical Attention.

---

#### **5: FIRE FIGHTING MEASURES**

**FIRE AND EXPLOSIVE PROPERTIES:**

Flash Point:	180°F TCC
Auto-ignition Temperature:	442°F Estimated
Lower Explosion Limit:	0.6 % Volume Estimated
Upper Explosion Limit:	21.0 % Volume Estimated

**Unusual Hazards:**

Potentially combustible liquid; may release invisible vapors that form combustible mixtures that might ignite or explode under some conditions. Vapors can travel considerable distances to an ignition source and flash back. Toxic gasses will form upon combustion. Material can accumulate static charges which can cause an incendiary electrical discharge. Material will emulsify and partially disperse and then float on water.

**Extinguishing Agents:**

Water spray, regular foam, dry chemical, carbon dioxide are appropriate. Use extinguishing media appropriate for surrounding media. Avoid spraying water directly into storage containers due to danger of boilover. Use water spray to cool adjacent fire exposed containers to avoid rupture and spattering.

**Personal Protective Equipment:**

Keep personnel removed and upwind. As in any fire, wear self contained breathing apparatus (pressure demand, MSHA/NIOSH approved or equivalent) and full protective gear.

**Special Procedures:**

Water may spread the fire.

---

## **6: ACCIDENTAL RELEASE MEASURES**

**Personal Protection:**

Appropriate protective equipment must be worn when handling a spill of this material. See the **PERSONAL PROTECTION MEASURES** Section for recommendations. If exposed to material during clean-up operations, see the **FIRST AID PROCEDURES** Section for appropriate actions.

**Procedures:**

Prevent ignition; stop leak; ventilate area; keep spectators away;

Flush small spills to sewer with plenty of water.

For large spills, contain spill immediately with inert noncombustible materials (e.g. sand, earth, absorbent). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal. Soak material with water to prevent any tendency of spontaneous combustion.

**CAUTION:** Keep large spills and cleaning runoff out of municipal sewers, watercourses and open bodies of water.

Use water spray to disperse vapors.

---

## **7: HANDLING AND STORAGE**

**Handling:**

Avoid contact with skin, eyes or clothing. Avoid breathing of mist or vapor.

Remove and wash contaminated clothing before reuse.

Practice good personal hygiene: Wash after handling; shower at end of work period.

**Storage Conditions:**

Keep away from heat, sparks and open flame. Protect from storage temperatures above 140°F.

Keep in a well ventilated space that is NFPA Class IIIA. Consult NFPA and OSHA codes.

Keep Out of Reach of Children.

Store upright in original closed container.

"Empty" containers retain product residue (liquid and/or vapor) that can be dangerous. Do NOT pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity or other sources of ignition due to explosion or fire hazard. Empty drums should be completely drained and properly bunged and promptly returned to a reconditioner or other proper disposal.

---

## **8: EXPOSURE CONTROLS, PERSONAL PROTECTION**

**Respiratory Protection:**

A respiratory program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Use of this product does not require respiratory protection under normal operating conditions but use of local exhaust ventilation is recommended, especially for confined spaces.

Where vapors or mists may occur, wear a MSHA / NIOSH approved (or equivalent) half-mask air purifying respirator. Air purifying respirators should be equipped with organic vapor cartridges and dust and mist filters.

**Eye Protection:**

Wear chemical splash goggles (ANSI Z87.1 or approved equivalent), or full face shield.

**Hand Protection:**

Wear gloves resistant to solvent permeation: neoprene, nitrile, polyvinyl alcohol, viton.

**Other Protection:**

None required.

**FACILITY CONTROL MEASURES:**

**Ventilation:**

Use with adequate ventilation. Local exhaust ventilation is recommended.

**Other Protective Equipment:**

Facilities storing or utilizing this material should be equipped with eyewash and safety shower facilities.

---

**9: PHYSICAL AND CHEMICAL PROPERTIES**

**TYPICAL**

State	Liquid
Appearance	Clear
Color	Colorless to very pale amber
Odor	Characteristic pleasant glycol
Viscosity	Thin < 5 cSt @ 25°C = 77°F
pH as is	Slightly acidic in water
Specific Gravity @ 60°F	0.981
Density @ 60°F	8.17 Lbs/Gal
Vapor Density (Air = 1)	< 1
Vapor Pressure	< 17 mm Hg @ 20°C = 68°F
Freezing Point	< 0°C = -32°F
Boiling Point	301°F initial
Solubility in Water	60% appreciable
Percent Volatility	95%
Evaporation Rate (BAc = 1)	0.2
VOC %	76% = 6.22 Lbs/Gal
HAP %	7% = 0.58 Lbs/Gal

---

**10: STABILITY AND REACTIVITY**

**Instability:**

This material is considered stable.

**Hazardous Decomposition Products:**

There are no known hazardous decomposition products for this material except for Carbon Dioxide, Carbon Monoxide if burned.

**Hazardous Polymerization:**

This product will not undergo polymerization.

**Incompatibility:**

This product is not compatible with strong acids and strong oxidizing agents.

---

**11: TOXICOLOGICAL INFORMATION**

Inhalation of large quantities of vapor for extended periods is presumed to be harmful: Overexposure to high concentrations can cause eye, nose, throat, lung irritation; dizziness, difficulty in breathing, unconsciousness.

Information available on the chronic health effects from long term exposure is limited.  
Skin contact can incur absorption. Repeated or prolonged contact is irritating.  
Eye contact is irritating.  
Oral consumption is harmful if swallowed. Pulmonary aspiration can enter lungs and cause damage.

---

## **12: ECOLOGICAL INFORMATION**

Toxic to fish and food organisms.

---

## **13: DISPOSAL CONSIDERATIONS**

### **Procedure:**

Incinerate liquid and contaminated solids in accordance with local, state and federal regulations.

---

## **14: TRANSPORTATION INFORMATION**

Proper Shipping Name: Not DOT Regulated in non-bulk containers

Hazard Class: None

Identification No.: None

Packing Group: None

Label: None

Emergency Response Guide No.: 27 / 128 Use as a guideline.

RQ: None

---

## **15: REGULATORY INFORMATION**

### **WORKPLACE CLASSIFICATIONS**

This product is considered to be hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### **EMERGENCY PLANNING AND COMMUNITY RIGHT - TO KNOW (SARA TITLE III)**

#### **Section 311/312 Categorizations (40 CFR 370)**

This product is a hazardous material under 29 CFR 1910.1200, and therefore is covered by Title III of SARA.

#### **Section 313 Information (40 CFR 372)**

This product contains a chemical which is listed in Section 313 at or above the de minimis concentrations:  
glycol ethers 33%

#### **CERCLA INFORMATION (40 CFR 302.4)**

Releases of this material to air, land or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to the state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

#### **RCRA INFORMATION**

When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability.

#### **CHEMICAL CONTROL LAW STATUS**

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

This Mixture is not considered to be a carcinogen by IARC or NTP.

This Solvent does NOT contain and is NOT manufactured with any of the Class I or Class II ozone depleting substances listed under the US Clean Air Act of 1990.

---

## **16: OTHER SUPPLEMENTAL INFORMATION**

### **ABBREVIATIONS**

<b>ACGIH</b>	<b>American Conference of Governmental Industrial Hygienists</b>
<b>OSHA</b>	<b>Occupational Safety and Health Administration</b>
<b>TLV</b>	<b>Threshold Limit Value</b>
<b>PEL</b>	<b>Permissible Exposure Limit</b>
<b>TWA</b>	<b>Time Weighted Average</b>
<b>STEL</b>	<b>Short Term Exposure Limit</b>
<b>BAC</b>	<b>Butyl acetate</b>
<b>NE</b>	<b>Not Established</b>
<b>ND</b>	<b>Not Determined</b>
<b>NA</b>	<b>Not Applicable</b>

---

The information contained herein pertains only to the specific material identified. Chemisphere Corp. believes that such information and recommendations set forth herein are accurate and reliable as of the date of this material safety data sheet, but Chemisphere Corp. makes no representation as to the completeness or accuracy thereof and supplies the information upon the condition that the persons receiving same will make their own determination as to its suitability for their purpose prior to use. In no event will Chemisphere Corp. be responsible for any damage of any nature whatsoever resulting from the use of or reliance upon this information. No representation, guarantee or warranty, either express or implied, is made hereunder as to the accuracy, reliability, completeness of the information, of merchantability, of fitness for a particular purpose or of any other nature, with respect to information or the product to which it refers.