



The Lawson Econo Flash

DESCRIPTION

Lawson Econo Flash Units gels most plastisol inks in 5-7 seconds and "cures" plastisol inks in 20 - 40 seconds.

All are adjustable in height to fit any press, include a handle to swing the I.R. Panel easily over your garment, include casters and are ETL approved. These flash units are "anti-tip" designed and all our manual flash units have positioning handles for easy rotation, from any direction. Plugs directly in to any standard grounded outlet - no temperature controller.

Standard Sizes

16" x 16" (120 volts)
18" x 18" (120 or 230 volts)
Custom sizes available on request

REASONS TO BUY

- ✓ Adjustable Temperature Controller (on all Super Flash Units): Control the temperature to match ink and flashing requirements.
- ✓ Anti-Tip & Adjustable Height Floor Stand: Position the I.R. element anywhere desired without fear of tipping.
- ✓ 1-Year Complete Parts Warranty: Flash cure with confidence, reliability and consistency.

LAWSON FLASH UNITS ALL FEATURE

- ✓ Even Flash Heating - Consistent heat radiating over entire element surface.
- ✓ Low profile design - Units easily fit into areas where clearances are critical.
- ✓ Easy Installation - Light weight modular design permits simple installation on stands, printers -over tabletops or conveyors.
- ✓ Solid State Temperature Controls - Variable heat controller permits infinite temperature settings from 0 - 100%.
- ✓ One Year Parts Warranty

STANDARD FEATURES

- Casters
- Adjustable Height
- 360 Degree Rotation Ability
- Anti-Tip Floor Stand
- 1-Year Heating Element Warranty
- National Safety Code Certified/ETL

OPTIONAL FEATURES

- Locking Floor Casters
- Digital Temperature Controller



LAWSON
SCREEN & DIGITAL PRODUCTS, INC.

5110 Penrose St. | St. Louis, MO 63115
314.382.9300 | 800.325.8317 | www.golawson.com

SPECIFICATIONS

	Cure Area	Temp Control	Electric	Casters	Warranty
Insta-Flash	16 x 16	Y	120 volts ,15 amps	Option	3 year
	16 x 16 w/ Air	Y	120 volts, 20 amps	Option	1 year
	20 x 20	Y	230 volts, 14 amps	Option	3 year
	20 x 20 w/ Air	Y	230 volts, 14 amps	Option	1 year
	12 x 24	Y	230 volts, 14 amps	Option	1 year
	12 x 36	Y	230 volts, 20 amps	Option	1 year
Econo-Flash	16 x 16	N	120 volts ,15 amps	Yes	1 year
	16 x 16	N	230 volts, 08 amps	Yes	1 year
	18 x 18	N	120 volts ,15 amps	Yes	1 year
	18 x 18	N	230 volts, 14 amps	Yes	1 year
Super Flash	16 x 16	Y	120 volts ,15 amps	Yes	1 year
	16 x 16	Y	230 volts, 08 amps	Yes	1 year
	18 x 18	Y	120 volts ,15 amps	Yes	1 year
	18 x 18	Y	230 volts, 14 amps	Yes	1 year
Hot Shot IR Manual	18 x 18	Y	230 volts, 16 amps	Option	1 year
Automatic Flash Units					
Quartz QZE Shuttle Flash	18 x 24	Dwell	230 volts, 22 amps	Yes	1 year
Roto Flash	16 x 16	Y	120 volts ,15 amps	Option	1 year
	18 x 18	Y	120 volts ,15 amps	Option	1 year
Hot Shot IR Shuttle	18 x 18	Y	230 volts, 16 amps	Option	1 year